**Basic equipment** 

with controller

Backtacking button

lifting and lowering

• Sewing head Brother S-7220C-403

• Integrated direct drive sewing drive

• AC voltage 190 V-240 V, 50/60 Hz

• Puller transport with pneumatic

• Machine frame of adjustable height

# EWS **6100**

## **Technical Specifications**

Dimensions	
Length	600 mm
Width	1100 mm
Height	
Treight	1200 11111
Table height	
Manually adjustable from	700 mm to 1.100 mm
Weight	
Basic equipment	110 kg
basic equipment	110 Ng
Compressed air	
•	20 MI/6 har
Nominal pressure	20 NI/6 bar
B .	
Power supply	
Rated voltage	
AC voltage	220V/50/60 Hz
Power consumption	0,7 kWh

# **Sewing System**

Maximum sewing speed	4000 rpm
Stitch length	0,5-4,2 mm
Needle system	134 R
Needle size	80-110 Nm

## **Examples of output**

Up to 600 trousers in 8 hours (depending on the seam length)





### Automated-Sewing-Systems AG

Am Beetacker 3 · 63856 Bessenbach Fon: +49 6095 99233-0 Fax: +49 6095 99233-20 E-Mail: info@assag.de Internet: www.assag.de

### More than 6,000 sewing machines worldwide

Since the year 2000, we develop and produce automatic sewing systems for the HAKA and DOB production and market them all over the world. Among others, our range of products include automatic piping pocket, closing seam and serging units as well as engineered workstation

Ranging from the development and construction right up to installation and programming, we complete all work steps in our company in Germany. In this manner, we can ensure uniform and consistently high quality in all stages of production.

Our sewing systems provide functional and process-optimised solutions. We develop small quantities of special machines for specific customer requirements. We shall be pleased to prepare a unique offer even for you.



## **Advantages**

Up to 600 trousers in 8 hours (depending on the seam length)

Simple operation


**Quick learning process** 




# EWS **6100**

# Designed workplace for stitching the waist in the seam shadow







The puller ensures optimal and prompt transport of the sewn material




Special presser foot for stitching in the shadow of the seam



Working table shaped for ease of production

# Sample seams

Here is an example of the seam







## Advantages

- ✓ Simple operation
- ✓ Quick learning process
- ✓ Up to 600 trousers in 8 hours (depending on the seam length)

## **Production Process**

The EWS 6100 is impressive with its easy operator navigation. With few settings, the machine can be set up for high production yield.

#### Program pre-selection:

The number of backtack stitches and the pulling speed of the puller transport are preset on the control panel.

#### Sewing procedure:

The sewing part is placed on the spring-loaded stop. The puller transport brings the waist in place. The sewing part can be sewn quickly over the rounded table guide. Back tacking can be switched on by pressing button, or automatically integrated in seam programm. The sewing operation is completed by cutting the thread automatically.

#### Work ergonomics:

The system can be operated as a workstation either in standing or sitting position. The height of the table can be adjusted to the body height of the operator.

## **Performance Profile**

The EWS 6100 is an optimally designed workplace for stitching trousers and skirt waistbands in shadow seam. The liberal procedure below the sewing base enables easy display of the sewing part.

The puller transport synchronised to the sewing speed stretches the sewing part and ensures a good seam quality. The pulling speed of the puller can be controlled smoothly and continuously and thus, it can be adjusted to any sewing material. The puller is lifted during by back tacking at the beginning and end of the seam. The number of back tacking stitches can be set on the control panel.